

Insulated Shackles


Part Numbers Listed Next to the Product Photographs



P/N 13692-D



P/N 10ARM300-14CN-3



P/N 10ARM300-15CN-1
For stranded wire only



P/N 10ARM300-14CN



P/N 10ARM300-37L-3



P/N 10ARM300-37L



Part Number	RF Breakdown (kV @ sea level)	Antenna Wire Attachment	Antenna Wire (P/N)	Maximum Load kg / (lbs.)	Length cm / (in)	Weight g / (Oz)	Attachment Means
13692-D	7.5	Chuck Jaws	14379	200.44 (450)	23.5 (9.25)	60.1 (2.12)	Shackle
13624-D	7.5	Chuck Jaws	14379	68.0 (150)	24.3 (9.56)	70 (2.47)	Shackle
10ARM300-14CN	10	Chuck Jaws	14379	113.40 (250)	14.3 (5.62)	24 (.85)	Eye
10ARM300-37L	10	Pass Thru Hole	14379	113.40 (250)	13.5 (5.30)	22 (.78)	Eye
10ARM300-14CN-3	10	Chuck Jaws	14379	200.44 (450)	14.9 (5.87)	24 (.85)	Quick Disconnect
10ARM300-37L-3	10	Pass Thru Hole	14379	200.44 (450)	14.3 (5.62)	22 (.78)	Quick Disconnect
10ARM300-15CN-1	10	*	16438	113.40 (250)	11.4 (4.5)	20 (.70)	Shackle