

NON-INSULATED TENSION UNIT

Part Numbers Listed Next to the Product Photographs

P/N 16644
P/N 13816
P/N 14818-2



P/N 12330-1
P/N 12330-2



P/N 5ARM300-11C
P/N 5ARM300-5C
P/N 5ARM300-6C
P/N 5ARM300-5CA
P/N 5ARM300-6CH



P/N 5ARM300-11CN
P/N 5ARM300-5C-3
P/N 5ARM300-6C-3
P/N 5ARM300-6C-1G
P/N 5ARM300-6C-3G
P/N 5ARM300-11C-3
P/N 5ARM300-11C-5
P/N 5ARM300-11C-6



Part Number	Spring Travel cm / (in)	Starting Force kg / (lbs)	Mid Stroke Force kg / (lbs)	Full Stroke Force kg / (lbs)	Maximum Load kg / (lbs)	Pre-set cm / (in)	Antenna Wire Attachment	Antenna Wire	Attachment Means	Length cm / (in)	Ground Strap	Weight g / (Oz)	Tube Diameter cm / (in)
14818-2	11.43 (4.5)	9.07 (20)	34.02 (75)	68.0 (150)	725.28 (1600)	5.71 (2.25)	Chuck Jaws	14379	Ball & Swivel	50.8 (20)	No	400 (14.1)	1.58 (.62)
13816	3.18 (1.5)	3.63 (8)	15.88 (35)	28.95 (65)	200.44 (450)	5 (2)	Chuck Jaws	14379	Ball & Swivel	24.13 (9.5)	No	100 (3.5)	1.58 (.62)
12330-1D	7.62 (3.0)	4.54 (10)	13.61 (30)	27.21 (60)	272.17 (600)	None	Chuck Jaw Pin	14379	Eye	38.1 (15)	No	140 (4.9)	1.58 (.62)
12330-2D	3.18 (1.5)	4.54 (10)	9.07 (20)	18.14 (40)	272.17 (600)	None	Chuck Jaw Pin	14379	Eye	30.48 (12)	No	110 (3.8)	1.58 (.62)
12330-3D	9.52 (3.75)	4.54 (10)	31.75 (70)	79.38 (175)	272.17 (600)	None	Chuck Jaw Pin	14379	Eye	45.72 (18)	No	230 (8.1)	1.58 (.62)
12330-1	7.62 (3.0)	4.54 (10)	13.61 (30)	27.21 (60)	272.17 (600)	None	Pin	14379	Eye	22.89 (9)	No	120 (4.2)	1.58 (.62)
12330-2	3.18 (1.5)	4.54 (10)	9.07 (20)	18.14 (40)	272.17 (600)	None	Pin	14379	Eye	16.51 (6.5)	No	96 (3.4)	1.58 (.62)
5ARM300-11C	3.18 (1.5)	2.27 (5)	6.80 (15)	9.07 (20)	226.80 (500)	None	Chuck Jaws	14379	Eye	15.24 (6)	No	50 (1.76)	1.11 (.44)
5ARM300-5C	2.54 (1.0)	4.54 (10)	9.07 (20)	13.61 (30)	226.80 (500)	None	Chuck Jaws	14379	Eye	15.24 (6)	No	50 (1.76)	1.11 (.44)
5ARM300-6C*	6.35 (2.5)	3.63 (8)	11.34 (25)	22.68 (50)	181.44 (400)	None	Chuck Jaws	14379	Eye	25.4 (10)	No	100 (3.5)	1.11 (.44)
5ARM300-11C-3	3.18 (1.5)	2.27 (5)	6.80 (15)	9.07 (20)	226.80 (500)	None	Chuck Jaws	14379	Quick Disconnect	16.51 (6.5)	No	50 (1.76)	1.11 (.44)
5ARM300-5C-3	2.54 (1.0)	4.54 (10)	11.34 (25)	13.61 (30)	226.80 (500)	None	Chuck Jaws	14379	Quick Disconnect	16.51 (6.5)	No	50 (1.76)	1.11 (.44)
5ARM300-6C-3	6.35 (2.5)	3.63 (8)	11.34 (25)	27.21 (60)	226.80 (500)	None	Chuck Jaws	14379	Quick Disconnect	26.67 (10.5)	No	100 (3.5)	1.11 (.44)
16644	3.18 (1.5)	3.63 (8)	15.88 (35)	29.48 (65)	181.44 (400)	5 (2)	Chuck Jaws	14379	Ball & Swivel	24.13 (9.5)	No	100 (3.5)	1.58 (.62)
5ARM300-6C-3G	6.35 (2.5)	3.63 (8)	11.34 (25)	27.21 (60)	181.44 (400)	None	Chuck Jaws	14379	Quick Disconnect	25.4 (10.37)	Yes	100 (3.5)	1.11 (.44)
5ARM300-6C-1G	6.35 (2.5)	3.63 (8)	11.34 (25)	27.21 (60)	226.80 (500)	None	Chuck Jaws	14379	Ball & Swivel	25.4 (10.37)	Yes	100 (3.5)	1.11 (.44)
5ARM300-11C-5	3.18 (1.5)	2.27 (5)	6.80 (15)	9.07 (20)	226.80 (500)	None	Chuck Jaws	14379	Quick Disconnect	16.51 (6.5)	Yes	50 (1.76)	1.11 (.44)

* 5ARM300-6CG with ground strap



P.O. Box 350550, Ft. Lauderdale, FL 33335

Tel: (954) 463-3451 Fax: (954) 761-3172

Website: www.daytongranger.com

E-mail: sales@daytongranger.com

SAI GLOBAL

ISO 9001:2015 + AS9100D

Rev. A