

STRAIN INSULATORS

Part Numbers Listed Next to the Product Photographs

P/N 12354
P/N 12354-1



P/N 13842
P/N 14392



P/N 10ARM300-13CN
P/N 10ARM300-18CN



P/N 14810



P/N 15733



P/N 12354D
P/N 12354-1D



Part Number	Voltage Breakdown (kV @ sea level)	Antenna Wire Attachment	Antenna Wire (P/N)	Maximum Load kg / (lbs.)	Insulation to Space (kV)	Diameter cm / (in)	Length cm / (in)
15733	18 @ 30,000 ft	Chuck Jaws	14809	378.61 (850)	180	2 (.805)	18.4 (7.25)
14810	7.5	Chuck Jaws	14809	362.90 (800)	180	1.6 (.625)	13.6 (5.37)
14392	10	Chuck Jaws	14379	181.44 (400)	180	1.6 (.625)	13.3 (5.25)
13842	7.5	Chuck Jaws	14379	181.44 (400)	180	1.6 (.625)	13.3 (5.25)
12354	5	Pin	14379	226.80 (500)	—	1.6 (.625)	11.7 (4.6)
12354-1	5	Pin	14379	226.80 (500)	—	1.6 (.625)	14.3 (5.26)
12354D	5	Chuck Jaw Pin	14379	181.44 (400)	—	1.6 (.625)	39 (15.37)
12354-1D	5	Chuck Jaw Pin	14379	181.44 (400)	—	1.6 (.625)	41.6 (16.37)
10ARM300-13CN	5	Chuck Jaws	14379	133.40 (250)	—	1.1 (.437)	13 (5.1)
10ARM300-18CN	5	Chuck Jaws	14379	133.40 (250)	—	1.1 (.437)	13 (5.1)